



# TECHNICAL DATA SHEET

## Schnell Synthlight SAE 5W-20

Advanced Low Viscosity Fully Synthetic

### Product Description:

Schnell Synthlight is a fully synthetic 5W20 engine oil specially formulated for engines having manufacturer recommendations of 0W20/5W20/0W30 grades to be used in all climates. Strengthened with Schnell Synthetic oil additives to provide superior protection and heat tolerance compared with regular low viscosity oils in the market. Increase power and lower fuel consumption.

Especially suited to WTI/VTEC variable valve train engines. Sustained horsepower and torque with superb engine smoothness throughout the life of your engine with regular use.

### Feature and Benefits:

- Ultra low viscosity designed for greater engine response
- Increased HP and torque, super smooth and quieter engine running
- Significantly lower friction with strengthened oil film
- Reduced CO2 emissions and improved fuel economy
- Lower emissions and exceeds Euro IV Spec
- Warning: Increasing performance of engine may result in greater engine wear

### Specifications :

ACEAA1/B1;APISN/CF;ILSACGF4;FordWSS948B

### Typical Properties:

SAE Grade:

5W-20

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	
Kinematic Viscosity @40°C	ASTM D445-10	cSt	
Kinematic Viscosity @100°C	ASTM D445-10	cSt	
Viscosity Index	ASTM D2270-04		
Flash Point, COC	ASTM D92-05a (10)	°C	
Pour Point	ASTM D97-09	°C	
Base Number	ASTM D2896-07a	mg KOH/g	

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.