

# TECHNICAL DATA SHEET

## Schnell DPF SAE 5W-30

Fully Synthetic Engine Oil for Diesel and Gasoline Engines with or without Turbo

### Product Description:

Schnell DPF SAE 5W-30 is a fully synthetic PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. Schnell additive technology reduces carbon or sludge build up even under severe driving conditions.

Schnell DPF SAE 5W-30 is manufactured using the highest quality Fully Synthetic base stocks and state of the art Schnell additive technology. This ensures a finished product with an unmatched performance level.

It is designed for advanced passenger car gasoline and diesel engines, both turbo-charged and non-turbo-charged including engines with diesel particle filters (ACEA C3)

### Specifications :

ACEAA3 / B4-04 / C3

API SM /CF

BMW Longlife-04 (OEM Approval) MB 229.51

Porsche C30

VW 504 00 / 507 00 (OEM Approval)

### Typical Properties:

SAE Grade:

0W-30

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg / L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	71.5
Kinematic Viscosity @100°C	ASTM D445	cSt	12.2
Viscosity Index	ASTM D2270		171
Flash Point, COC	ASTM D92-05A	°C	230
Pour Point	ASTM D97	°C	-39