

TECHNICAL DATA SHEET

Schnell Multiturbo SAE 20W-50

For Diesel and Gasoline engine with or with Turbo Mineral Base universal engine oil

Product Description:

Advanced formulation, manufactured using the highest quality first refined German mineral base oil stock. Schnell Multiturbo SAE 20W-50 is a high stability viscosity engine oil that protects against friction, heat and corrosion. Keeping engines healthy and efficient. Schnell Multiturbo SAE 20W-50 additives reduces carbon and sludge build-up even under severe driving conditions. Engines run quieter and smoother throughout with regular use.

Feature and Benefits:

Schnell additives reduces carbon and sludge build even under severe driving conditions. Engines run quieter and smoother through our with regular use.

- High flash point (>180oC)
- Smoother and quieter engine running
- Lower friction with strong oil film
- Reduced CO2 emissions and improved fuel economy
- SuperTurbo Engine Oil Formulation for all modern Engine

Specifications :

API CH-4 / SM;
ACEAA3/B3/E2;
MB 229.1;
VW501.01 / 505.00

Typical Properties:

SAE Grade:

20W-50

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8834
Kinematic Viscosity @40°C	ASTM D445-10	cSt	175.0
Kinematic Viscosity @100°C	ASTM D445-10	cSt	20.96
Viscosity Index	ASTM D2270-04		141
Flash Point, COC	ASTM D92-05a (10)	°C	235
Pour Point	ASTM D97-09	°C	-33
Base Number	ASTM D2896-07a	mg KOH/g	8.20

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.