

TECHNICAL DATA SHEET

Schnell LL SAE 5W-30

Advance Longlife Low Emission Fully Synthetic Engine Oil

Product Description:

Schnell LL SAE 5W-30 is premium fully synthetic and PAO-based formulated engine oil. It is specially developed for use in the latest generation of low-emission gasoline and diesel engines and offers improved fuel economy especially when equipped with diesel particulate filters, catalytic converters, turbo-charged and Exhaust Gas Recirculation (EGR) devices.

It is suitable for all modern Audi and VW diesel and gasoline engines requiring VW 504.00 / 507.00 specifications, and provides strong protection for modern FSI, TDI and turbo-charged engines.

Feature and Benefits:

- Fully synthetic formula that provides excellent wear protection and prevent deposit and sludge build-up to enhance engine life
- Outstanding thermal and oxidation stability during the maximum oil change interval according to manufacturer recommendation
- Reduce emissions and exceeds Euro IV and Euro V emission standards
- Outstanding cold start properties for ultra fast engine protection
- Advanced friction reducing formulation for enhance fuel economy

Specifications:

API SP/SQ, ACEA C3, approved BMW Longlife-04, MB 229.51, Porsche C30 approved under VW Standard 504 00 and VW Standard 507 00

Typical Properties: SAE Grade: 5W-30

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8564
Kinematic Viscosity @40°C	ASTM D445-10	cSt	71.9
Kinematic Viscosity @100°C	ASTM D445-10	cSt	11.09
Viscosity Index	ASTM D2270-04		151
Flash Point, COC	ASTM D92-05a (10)	°C	230
Pour Point	ASTM D97-09	°C	-45
Base Number	ASTM D2896-07a	mg KOH/g	6.4