



TECHNICAL DATA SHEET

Schnell Ultimate II SAE 5W-40

Advanced High Performance Fully Synthetic Engine Oil

Product Description:

Schnell Ultimate II SAE 5W-40 Fully Synthetic formulation protects against friction, heat and corrosion, keeping engines healthy and efficient. Schnell additives reduce carbon and sludge build up even under severe driving conditions.

Schnell Ultimate II SAE 5W-40 has an excellent range of applications; ranging from K class engines to WTI / VTEC engines to European engines. Appropriate for use in turbo-charged car giving improved engines quietness and reduced emissions. Sustained horsepower and torque throughout the life of your engine with regular use.

Schnell Ultimate II SAE 5W-40 is manufactured using the highest quality Fully Synthetic base stocks and state of the art Schnell technology. This ensures a finished product with an unmatched performance level.

Specifications :

ACEA A3 / B3; API SN / CF; MB 229.1; VW 501 01 / 505 00; BMW LL-98

Typical Properties:

SAE Grade:

5W-40

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052	kg / L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	89, 52
Kinematic Viscosity @100°C	ASTM D445	cSt	14, 6
Viscosity Index	ASTM D2270		170
Flash Point, COC	ASTM D92-05a	°C	> 200
Pour Point	ASTM D97	°C	< -38

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.