

Schnell Ultimate III SAE 5W-50

Fuel Saving Fully Synthetic Engine Oil for All Gas Engine Cars

Product Description:

Schnell Ultimate III SAE 5W-50 is a fully synthetic that protects against friction, heat and corrosion, keeping gas engines healthy and efficient. Schnell Ultimate III SAE 5W-50 reduces carbon and sludge build-up even under severe driving conditions. It is a fully synthetic SAE 5W-50 engine oil specially formulated for all CNG engines, especially in Tropical Climates

Feature and Benefits:

- Fully synthetic high viscosity PAO-Ester base stock formula for superior wear protection and low oil consumption
- High heat stability, especially recommended for performance and modified engines
- Special additive formulation that provides high wear protection with reduce friction for excellent start up and high rpm wear protection

Specifications :

API SP
VW 502.00 / 505.00L
MB 229.1, 229.3
BMW
Porsche

Typical Properties:

SAE Grade:

5W-50

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8565
Kinematic Viscosity @40°C	ASTM D445-10	cSt	117.78
Kinematic Viscosity @100°C	ASTM D445-10	cSt	17.99
Viscosity Index	ASTM D2270-04		170
Flash Point, COC	ASTM D92-05a (10)	°C	235
Pour Point	ASTM D97-09	°C	-42
Base Number	ASTM D2896-07a	mg KOH/g	8.76

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.
All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication.
The information contained herein is subject to change without notice.