

TECHNICAL DATA SHEET

Schnell Ultimate II SAE 0W40

Fully Synthetic High Performance Multigrade Engine Oil

Product Description:

Schnell Ultimate II SAE 0W40 is a fully synthetic PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. Schnell additives reduces carbon or sludge build up even under severe driving conditions. Top-class fully synthetic fuel-economy multi-grade motor oil.

Specifications :

ACEA A3 / B4;
 API SN / CF;
 BMW LL-01;
 MB 229.5;
 PSA B71 2296;
 VW 502 00 / 505 00;
 Renault RN 0700 / RN 0710;
 Porsche A40

Typical Properties:

SAE Grade:

0W40

Test	Method	Unit	Result
Density at 15°C	ASTM D4052-09	kg / L	0.854
Kin. Viscosity at 40°C	ASTM D445-10	cSt	81.7
Kin. Viscosity at 100°C	ASTM D445-10	cSt	14.2
Viscosity Index	ASTM D2270-04	-	180
Flash Point COC	ASTM D92-05a (10)	°C	242
Pour Point	ASTM D97-09	°C	- 44
Base Number	ASTM D2896	mg KOH/g	10.5

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.