

TECHNICAL DATA SHEET

Schnell Ultimate TS SAE 10W-40

Synthetic Light- Running Engine Oil for All Modern Cars

Product Description:

Schnell Ultimate TS SAE 10W-40 is a Semi-synthetic fuel-economy multi-grade motor oil formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. Advanced additives reduces carbon or sludge build-up even under severe driving conditions. For use in passenger car gasoline and diesel engines.

Features & Benefits

- Low oil consumption
- High level of performance base oil composition with semi-synthetic oil.
- Special for use in passenger car gasoline and diesel engines, with or with out turbocharging

Specifications :

ACEA A3 / B3 / B4-04 API SL / CF

MB 229.1

VW 501 01 / 505 00

Typical Properties:

SAE Grade:

5W-40

Test	Method	Unit	Result
Density @ 15°C	ASTM D4052-09	kg / L	0.8667
Kinematic Viscosity @40°C	ASTM D445-10	cSt	100.6
Kinematic Viscosity @100°C	ASTM D445-10	cSt	14.89
Viscosity Index	ASTM D2270-04		155
Flash Point, COC	ASTM D92-05a (10)	°C	247
Pour Poin	ASTM D97-09	°C	-39
Base Number	ASTM D2896-07a	mg KOH/g	8.0

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty or representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.